

S6A3-MPTAW 221 - 385 kW | PROPULSION IMO TIER II

MITSUBISHI MARINE ENGINE

RELIABLE MECHANICAL ENGINE

ENGINE DATA	
Engine model	S6A3-MPTAW
Cylinder configuration	6 in-line
Total displacement	18.56
Bore x stroke (mm)	150 x 175
Flywheel and housing	SAE 14 / SAE 10
Compression ratio	14.5:1
Dry weight (kg)	1900



cooling circuit; charge air Cooling method cooler by closed freshwater		
cooling circuit; charge air Cooling method cooler by closed freshwater	Method of operation	engine, with direct-injection,
system controlled by thermostat (intercooler)	Cooling method	cooler by closed freshwater system controlled by thermostat

RATING ^{1,2}			
Rating	UCD	HD	MD
Output (kW)	221	360	385
Output (bhp)	296	483	516
Engine speed (rpm)	1530	1840	1800
Emissions		IMO Tier II	

¹For rating definitions, please see our website.
²Atmospheric condition: barometic pressure: 100kPa, ambient temperature: 298K, relative humidity: 30%.



STANDARD AND OPTIONAL EQUIPMENT

STANDARD EQUIPMENT

Governor (mandatory)

• Mechanical governor, RSUV type

Fuel system

- Flexible fuel supply and return hoses
- Fuel feed pump
- Fuel fine filters, change-over type
- Fuel injection pump
- Dual walled high-pressure fuel lines
- Fuel injectors

Lubricating oil system

- Wet type oil pan with inspection covers
- Oil pressure pump, gear driven
- Lubricating oil filters, change-over type
- By-pass filter
- Oil cooler with thermostat

Starting and electrical system

- Electric starter (Earth floated 24V)
- Alternator, 30 Amps.
- Stop solenoid (ETS)

Cooling system

- Freshwater pump including piping and thermostat (HT)
- Front pulley PTO standard

Air inlet system

- Mitsubishi turbocharger
- Air inlet silencer with pre-cleaner
- Inlet air aftercooler or intercooler
- Inlet manifolds or ducts

Other

- Mounting brackets for rigid mounting
- Flywheel and housing, SAE standard
- Torsional vibration damper

OPTIONAL EQUIPMENT


Classification


We are cooperating with many of the major classification societies.

Exhaust system

- Stainless steel insulation (SOLAS)
- Flexible expansion joint

DIMENSIONS





More information

MOVE THE WORLD FORW➤RD MITSUBISHI

CS-M-S6A3-MPTAW-2102V1.0